

# ECS-DUAL50W / ECS-DUAL50WB

## 50/100 Watt Dual Channel Amplifier with optional Backup Amplifier

The ECS-DUAL50W (red) and ECS-DUAL50WB (black) are intelligent 50 / 100 watt amplifier for use with the IFP-100ECS, IFP-300ECS, IFP-1000ECS, IFP-2000ECS or IFP-2100ECS. The ECS-DUAL50W is used to amplify audio message for distribution throughout a facility.

The ECS-DUAL50W is capable of producing up to 100 watts of audio power. The ECS-DUAL50W has its own power supply with battery backup and eight speaker circuits. The ECS-DUAL50W is fully supervised by the main panel for trouble conditions.

### Installation

The ECS-DUAL50W can be surface or flush mounted.

### Compatibility

The ECS-DUAL50W is compatible with the following voice evacuation components:

- IFP-100ECS
- IFP-300ECS
- IFP-1000ECS
- IFP-2000ECS
- IFP-2100ECS

Note: Dual channel is only compatible with IFP-2000ECS, IFP-300ECS or IFP-2100ECS



**ECS-DUAL50WB**

## FEATURES & BENEFITS

- Amplifier is compatible as: 50W with 50W as backup
- 100 W single channel
- 100 W single channel with 50 W backup using ECS-50WBU
- Dual channel using 50W for each channel (IFP-2000ECS or IFP-2100ECS only)
- Dual channel 50 W each channel with 50 W backup using ECS-50WBU
- Amplifier Bandwidth 400Hz to 4000Hz
- Built in backup amplifier test feature allows you to physically test that the backup amplifiers are operating properly
- The ECS-DUAL50W has it's own power supply and backup battery
- Can be mounted up to 6000 feet away from ECS-Series control panel
- 120VAC or 240VAC operation
- Available in a red or black cabinet
- UL 864 and UL 2572
- UL listed for 520Hz signaling when used with compatible speakers
- Up to 16 amplifiers per IFP-2000ECS or ECS-2100ECS system for a maximum of 1600 watts
- Distributed between up to 128 audio circuits

# ECS-DUAL50W Technical Specifications

## PHYSICAL

**Flush Mount Dimensions:** 14.5"W x 24.75"H x 3.4"D (36.8 W x 62.9 H x 8.7 D cm)

**Overall Dimensions:** 16.1"W x 26.5"H x 4.1"D (40.64 W x 66.7 H x 10.5 D cm)

**Color:** Red or Black

## ENVIRONMENTAL

**Operating Temperature:** 32°F to 120°F (0°C to 49°C)

**Humidity:** 10% to 93% relative humidity (non-condensing)

## ELECTRICAL

**Primary AC:** 120VAC @ 60Hz

**ECS-DUAL50W 25V:** 190mA standby current

**ECS-DUAL50W 70V:** 190mA standby current

**ECS-DUAL50W 25V:** 2380mA alarm current

**ECS-DUAL50W 70V:** 2470mA alarm current

**Primary AC:** 240V @50Hz

**ECS-DUAL50WHV 25V:** 200mA standby current

**ECS-DUAL50WHV 70V:** 200mA standby current

**ECS-DUAL50WHV 25V:** 1260mA alarm current

**ECS-DUAL50WHV 70V:** 1310mA alarm current

**Total Power:** 100 W @ 25 VRMS or 70.7 VRMS

- **Circuit 1-4:** 50W max.
- **Circuit 5-8:** 50W max

**Main ECS Panel SBUS Standby & Alarm:** 10mA

**Battery Charging Capacity:** 7 – 35AH

**Battery Size:** 18AH max allowed in cabinet. Use RBB accessory cabinet for larger batteries up to 35AH per system.

## Voice Integration Wiring:

- Six conductor
- Two voice bus
- Four SBUS

## ORDERING INFORMATION

**ECS-DUAL50W:** Intelligent 50 Watt Amplifier, Red

**ECS-DUAL50WB:** Intelligent 50 Watt Amplifier, Black

**ECS-DUAL50WHV:** High Voltage (240VAC) 50/100 Watt Dual Channel Amplifier.

## ACCESSORIES

**ECS-50WBU:** External Backup Amp.

**RBB:** RBB Remote Battery Box Cabinet. Use for backup batteries up to 35AH. 16" W x 10" H x 6" D

## AGENCY LISTINGS

**NFPA 13, NFPA 70, NFPA 72, UL 2572, UL 1711 & UL 864:** Local Protective Signalling Systems

**UL Listed**

**CSFM:** 7165-0559:0174

**FDNY COA:** (pending)

For a complete listing of all compliance approvals and certifications, please visit [www.farenhyt.com](http://www.farenhyt.com).

Microsoft, Windows, and the Windows Logo are registered trademarks or trademarks of Microsoft Corporation.

Honeywell® is a registered trademark of and Farenhyt™ is a trademark of Honeywell International, Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

For Technical Support, Please call 800-446-6444.

## For more information

Learn more about Honeywell's Farenhyt Series and other products available by visiting [www.farenhyt.com](http://www.farenhyt.com)

## Honeywell Security & Fire

12 Clintonville Road  
Northford, CT 06472  
800-328-0103