

Velociti Series® AOM-2RF

Addressable Output Relay Control Module

General

The Gamewell-FCI Velociti® Series, addressable output relay control module (AOM-2RF) allows a Gamewell-FCI analog addressable fire alarm control panel to switch discrete relay contacts by code command. The relay provides two isolated sets of Form-C contacts which transfer simultaneously. Circuit connections to the relay contacts are not supervised by the module.

The Velociti® Series use a communication protocol that substantially increases the speed of communication between the SLC devices and certain Gamewell-FCI analog addressable fire alarm control panels. These devices operate in a grouped fashion. If one of the devices in the group has a status change, the panel's microprocessor stops the group poll and concentrates on the single device. The net result produces a superior response speed up to five times greater than earlier designs.

The AOM-2RF Module is designed for installation in the signaling line circuit of any Gamewell-FCI analog addressable fire alarm control panel. The module contains a panel controlled LED. The AOM-2RF is designed to mount in a 4" (10.16 cm) square junction box 2 1/8" (5.53 cm) deep.

Ordering Information

AOM-2RF: Addressable output relay control module

Table 1 lists the relay contact ratings.

CURRENT RATING	MAXIMUM VOLTAGE	LOAD DESCRIPTION	APPLICATION
3A	30 VDC	Resistive	Non-Coded
2A	30 VDC	Resistive	Coded
0.9A	110 VDC	Resistive	Non-Coded
0.5A	125 VAC	Resistive	Non-Coded
0.5A	30 VDC	Inductive (L/R=5ms)	Coded
1A	30 VDC	Inductive (L/R=2ms)	Coded
0.5A	125 VAC	Inductive (PF=.35)	Non-Coded
0.7A	75 VAC	Inductive	Non-Coded

Table 1: Relay Contact Ratings



AOM-2RF

FEATURES & BENEFITS

- Listed under UL® Standard 864
 - Offers two sets of Form "C" contacts
 - Provides visual rotary, decimal switch addressing (01-159)
 - Includes a bi-color LED that flashes green whenever the module is addressed, and lights steady red upon activation*
 - Designed as a compact size to allow easy installation
- Note 1: Only the red LED is operative in panels that do not operate in Velociti® mode
*Note 2: The bi-color LED functionality is not available on the GWF-7075 panel.

Velociti Series® AOM-2RF Technical Specifications

SYSTEMS

Supervisory Current: .000375 amps.

Average Operating Current:

255 uA (Velociti Mode)

230 uA (CLIP Mode)

Alarm Current: .0065 amps.

Operating Temperature: 32° to 120° F (0° to 49° C)

Relative Humidity: 10 to 93% relative humidity (non-condensing)

Dimensions: 4 1/2" H x 4" W x 1 1/4"
(11.4 x 10.2 x 3.2 cm)

TEMPERATURE AND HUMIDITY RANGES

This system meets NFPA requirements for operation at 0 – 49°C/32 – 120°F and at a relative humidity 93% ± 2% RH (noncondensing) at 32°C ± 2°C (90°F ± 3°F).

However, the useful life of the system's standby batteries and the electronic components may be adversely affected by extreme temperature ranges and humidity. Therefore, it is recommended that this system and its peripherals be installed in an environment with a normal room temperature of 15 – 27°C/60 – 80°F.

STANDARDS

The Velociti Series® AOM-2RF is designed to comply with the following standard:

UL Standard: UL 864 9th Edition

AGENCY LISTINGS AND APPROVALS

These listings and approvals apply to the modules specified in this document. In some cases, certain modules or applications may not be listed by certain approval agencies, or listing may be in process. Consult factory for latest listing status.

UL: S1913

FM: 3023594

FDNY: COA-219-02-E Vol. VI

CSFM: 7300-1703:0102

ISO 9001 Certification

For a complete listing of all compliance approvals and certifications, please visit: <http://www.gamewell-fci.com/en-US/documentation/Pages/Listings.aspx>

Velociti® Series and Gamewell-FCI® are registered trademarks of Honeywell International Inc.

UL® is a registered trademark of Underwriter's Laboratories Inc.

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice.

For more information

Learn more about Gamewell-FCI's Velociti Series® AOM-2RF and other products available by visiting www.Gamewell-FCI.com

Honeywell Gamewell-FCI

12 Clintonville Road

Northford, CT 06472-1610

203.484.7161

www.honeywell.com

9020-0625 | | 04/19
©2019 Honeywell International Inc.

Honeywell