

COMMERCIAL HVAC COMPONENTS

Selection Guide for Valves, Actuators, Dampers and VFDs



Honeywell

THE HVAC PERFORMANCE YOU TRUST

At Honeywell, an HVAC component is never “just a part,” because we never stop looking for ways to improve the value each one brings to your operations. Throughout the world, hundreds of utilities, thousands of industrial facilities, and more than 100 million buildings rely on Honeywell valves, actuators, and electronic field devices for long-lasting efficiency, with hassle-free installation and performance.

Our comprehensive range of components ensures you have the tools you need for any application – and this guide will help you quickly find the ones you need.

CONTROL VALVES



PRESSURE INDEPENDENT CONTROL VALVES

Deliver high efficiency in less time

VRN Threaded Pressure Independent Control Ball Valves

- Maintains flow under varying differential pressures; increases coil differential temperature which improves the efficiency of the system
- Integrated pressure control cartridge combines circuit balancing and control functions in one package, resulting in consistent temperature and comfort
- Field serviceable stem and pressure regulating cartridge allow for easy serviceability for reduced life cycle costs
- 5-year warranty

- ZONE CONTROL
- RTU/AHU
- MECH ROOM



VRW Flanged Pressure-Regulating Control Valves

- Combination ANSI/ASME Class 150/300 flange connections
- Positive pressure, rolling diaphragm regulator design for long service life provides flow control accuracy of $\pm 5\%$
- 50 discrete, selectable flow rates available per valve size

- RTU/AHU
- MECH ROOM

PRESSURE INDEPENDENT CONTROL VALVE SELECTION GUIDE

Name	Size/Connection	Medium	Cv	Valve Body Pattern	Actuation	Close-off
VRN	1/2" to 3" NPT	Closed loop chilled or hot water	1 to 95 GPM	2-way	Modulating, floating and two position control in both fail-safe and fail-in-place	100 psi
VRW	2 1/2" to 6" ANSI 150/300 wafer-flanged	Closed loop chilled or hot water	113 to 468 GPM	2-way	Modulating and floating control in both fail-safe and fail-in-place	100 psi

CONTROL BALL VALVES

Cover every application with one control valve brand



VBN Threaded Control Ball Valves

- Characterized insert is integral to the ball, not outside the ball: results in longer service life and higher operating differential pressure capabilities
- Weather-proof enclosures available for outdoor rooftop applications
- Packless field-replaceable stem for easy service in pipe
- 5-year warranty


- ZONE CONTROL
- RTU/AHU
- MECH ROOM



VB6 6-way Control Ball Valves

- Class-leading specifications for temperature, close-off pressure, static pressure, and leakage
- Extremely compact, side-by-side design with zero leakage close-off
- Modular configuration providing 80 combinations of Cvs in 1/2 and 3/4 inch sizes
- 5-year warranty

- ZONE CONTROL




VBF Flanged Control Ball Valves

- Parabolic flow insert provides equal percentage flow for better control
- Weather-proof enclosures available for outdoor rooftop applications
- Globe valve layout with side B-port allows for easy retrofit

- RTU/AHU
- MECH ROOM

CONTROL BALL VALVE SELECTION GUIDE

Name	Size/Connection	Medium	Cv	Valve Body Pattern	Actuation	Close-off
VBN	1/2" to 3" NPT	Closed loop chilled or hot water	0.33 to 266	2-way or 3-way	Modulating, floating and two-position control in both fail-safe and fail-in-place	100 to 130 psi (2-way), 40 to 50 psi (3-way)
VB6	1/2" and 3/4" NPT	Closed loop chilled or hot water	0.3 to 14	6-way	Modulating fail-in-place	200 psi
VBF	4" to 6" ANSI 125/150 flanged	Closed loop chilled or hot water	91 to 650	2-way or 3-way	Modulating, floating and two-position control in both fail-safe and fail-in-place	70 psi



CARTRIDGE GLOBE VALVES

High performance in a compact design

V58 Series Cartridge Globe Valves

- Linear valve operation offers greater control, with constant load on the stem yielding decreased hysteresis
- Brass body and stainless-steel stem
- Field replaceable cartridges rebuilds valves in-pipe

● ZONE CONTROL



GLOBE VALVES

Precise control for any application Valves

V5011N 2-way and V5013N 3-way Threaded Globe Valves

- Excellent control
- Equal percentage flow characteristic available for water service and linear flow characteristic available for steam
- Offers best in class size, Cv range and close-off pressure
- Available with brass or stainless steel trim

● ZONE CONTROL

● RTU/AHU

● MECH ROOM



VGF Flanged Globe Valves

- ANSI Class 125 and Class 250 flanged cast iron bodies
- Differential pressure of 175 psi, ANSI Class IV leakage on pressure-balanced models
- Stainless steel trim
- Equal percentage and linear flow characteristics to ensure precise control in a variety of applications

● RTU/AHU

● MECH ROOM

GLOBE VALVE SELECTION GUIDE

Name	Size/Connection	Medium	Cv	Valve Body Pattern	Actuation	Close-off
V58	1/2" to 1 1/2" NPT or Sweat	Closed loop chilled or hot water	0.19 to 25	2-way or 3-way	Modulating, floating and two-position control in both fail-safe and fail-in-place	6.25–232 psi
V5011N, V5013N	1/2" to 2" NPT	Closed loop chilled or hot water and steam (2-way)	0.73 to 46.8	2-way or 3-way	Modulating, floating and two-position control in both fail-safe and fail-in-place	up to 230 psi water, up to 100 psi steam
VGF	2 1/2" to 6" ANSI 125 or ANSI 250 flange	Closed loop chilled or hot water and steam (2-way)	70 to 370	2-way or 3-way	Modulating, floating and two-position control in both fail-safe and fail-in-place	up to 175 psi water, up to 100 psi steam



BUTTERFLY VALVES

Powerful performance with impressive features

V58 Series Cartridge Globe Valves

- Full Cut Disc with bubble tight 200psi close-off (150psi for 14 inch valves and larger)
- MB Series Actuators available separately for retrofit and repair
- Fail-Safe Options with NEMA4X enclosure available to 12-inch valve size, both 2-way and 3-way
- Ductile iron valve body for superior strength
- 5-Year Warranty on valves up to 12 inch size, 2-year warranty on larger sizes

MECH ROOM



VH Series High Performance Butterfly Valves

- ANSI Class 150 High Performance valves with 285psi maximum pressure rating for high rise applications
- Can be used in saturated steam applications up to 50psi pressure
- Fail-Safe Actuation available up to 6-inch valve size in 2-Way, and 3-inch valve size in 3-Way
- 5-Year Warranty on 2-way valves up to 6 inch size, and 3-way valves up to 4-inch size, 2-Year Warranty on larger sizes

MECH ROOM

BUTTERFLY VALVE SELECTION GUIDE

Name	Size/Connection	Medium	Cv	Valve Body Pattern	Actuation	Close-off
VR	2"-24" (2-way) and 2"-18" (3-way) ANSI 125/150 compatible lugged	Chilled, hot or condenser water	115 to 43116	2-way or 3-way	Modulating, floating and two-position control in both fail-safe (up to 12") and fail-in-place	150 to 200 psi
VH	2"-24" (2-way) and 2"-16" (3-way) ANSI 150 lugged	Chilled, hot or condenser water and steam	102 to 22050	2-way or 3-way	Modulating, floating and two-position control in both fail-safe (up to 6" 2-way and 3" 3-way) and fail-in-place	150 psi, 50 psi steam

VALVE AND DAMPER ACTUATORS



MVN ACTUATORS

Get the job done on time and under budget

VRN Threaded Pressure Independent Control Ball Valves

- Click-on assembly cuts installation time - no tools needed
- Position indicator shows the open or closed position of the stem or ball valve for easy commissioning
- Compact design saves space allowing installation in confined areas
- Use with control ball valves & pressure independent control ball valves up to 1-1/4 inch
- Available with optional one or three meter cables for flexible installations
- 5-year warranty

MS AND MN ACTUATORS

Precise, reliable performance. Lasting value



- Self centering shaft adaptor reduces installation time and provides greater clamping force
- Decreased material cost due to detachable access cover
- Reduce inventory and selection time with signal mode adaptor that adapts models to two position, floating and modulating applications
- Increase control and accuracy with more than 200 reposition steps for modulating models provide precise control
- Select models are available with or without three foot actuator cable
- 5-year warranty

MS and MN SERIES NAMING STRUCTURE

MS 75 10 A 2 2 XX

Fail Safe Mode

MS Spring Return
MN Non-Spring Return

Input Signal Type

31 Syk Enabled, 24 Vac
41 Two-position, 100-250 Vac
61 Floating, 24 Vac
71/72 Modulating only, 24 Vac
74 Economizer/Modulating, 24 Vac
75 Modulating/Floating, 24 Vac
81 Two-position, 24 Vac

Torque

03 Nm - 27 in-lb
05 Nm - 44 in-lb
10 Nm - 88 in-lb
20 Nm - 175 in-lb
34 Nm - 300 in-lb

System Controlled Numbers

Auxiliary Switches

0 No Internal Switches
1 One Internal Switch
2 Two Internal Switches

Feedback

1 No Feedback
2 Voltage Feedback

Application Type

A Standard Model
H Enhanced Model
J Communicating Model

SMARTVFD HVAC

Easy installation. Easy commissioning. Great energy savings.



- **Start-Up Wizards** – All you have to do is tell the VFD whether you have a pump or a fan, enter nominal motor information, and you are up and running.
- **Graphic Interface** – The easy-to-use keypad and interface deliver menu-driven programming and monitoring for fast, uniform commissioning. Plus, a manual is built into the keypad for easy access when needed.
- **Built-In Communications** – With BACnet®, N2 and Modbus built in, you get a lower total installed cost and reliable communication with the building management system.
- **PC Software Wizards** – Commissioning, programming and troubleshooting are all a snap thanks to these guided Startup and PID wizards.
- **Built-In PLC** – Eliminates the need for an expensive external controller.
- **DC Choke** – For harmonic protection.
- **Standard RFI Filter** – Ensures that EMC/RFI requirements are met.
- **Real-Time Clock** – Battery included.
- **Fire Mode** – For safe operation.
- **Motor Switch Ride-Through** – Easy, fault-free maintenance.
 - 3 phase, 208/230 Vac, 0.75 to 125 nominal HP.
 - 3 phase, 480 Vac, 1.5 to 250 nominal HP.

SmartVFD HVAC/SmartVFD BYPASS NAMING STRUCTURE

HVFDSD 3 C 0100 G 1 0 0 A

Product Family

HVFDSD = Honeywell SmartVFD HVAC
 HVFDSB = Honeywell SmartVFD BYPASS

Input Phase

3 = Three Phase (3~in, 3~out)

Nominal Voltage

A = 208/230 Vac Drive Alone, 208 Vac Bypass
 B = 230 Vac Bypass
 C = 480 Vac
 D = 575 Vac

Nominal Horsepower

0007 = .75 Horse Power
 0010 = 1 Horse Power
 0100 = 10 Horse Power

A = Updated Control Board
 No A = Legacy Control Board

Options

0 = Drive Only or No Special Options
 1 = Auto-Bypass
 3 = Auto-Bypass and HOA

Contactors

0 = Drive Only
 1 = Disconnect Only
 2 = Two Contactor Bypass
 3 = Three Contactor Bypass

Enclosure Type

1 = NEMA 1
 2 = NEMA 12
 3 = NEMA 3R

Interface

G = Graphic Keypad

SMARTVFD BYPASS

Easy to specify, select, install and commission: The SmartVFD BYPASS is the perfect complement to the advanced capabilities of the SmartVFD family.



Precise, reliable performance. Lasting value

Our five configurations make it easy to select the right bypass to complete your drive package. All bundles are available in NEMA 1, NEMA 12 and ventilated NEMA 3R.

SmartVFD Disconnect Option

- Adds a fused disconnect to the VFD

SmartVFD 2-Contactor Bypass Option

Provides an economical means of bypassing the VFD.

- No Main Disconnect
- Freeze/Fire/Smoke Interlock

SmartVFD 3-Contactor Bypass Option

During commissioning, the TEST position enables power-up of the VFD without sending power to the motor.

- In Bypass mode, the VFD is isolated from the power supply
- Fused Disconnect
- Freeze/Fire/Smoke Interlock

SmartVFD 3-Contactor Auto-Bypass Option

All the features of the 3-Contactor bypass plus:

- Any VFD fault will automatically send the bypass to bypass mode
- A contact closure sends the bypass to bypass mode
- A contact closure sends the bypass to bypass mode
- Dry contacts indicate when the bypass is in bypass

SMARTVFD HVAC2



SmartVFD HVAC2 Spins Big Energy Savings

The SmartVFD HVAC2 drive is a micro drive designed to fit in your enclosure or become a NEMA 1 enclosure – whichever is required for your smaller frequency drive applications.



Modular Design

- NEMA 1 kit available
- Optional EMC filter
- Accessory PC interface

Easy to Install

- DIN-rail or screw mounting
- Zero clearance side-by-side mounting

Easy Communication

- Intuitive user interface
- Accessory PC interface
- Free PC Tool with optional adaptor turns your computer into a programming window to setup, control, monitor and diagnose in real time or for off-line editing and backup
- PI control
- Modbus RTU

Rugged, High Performance

SmartVFD HVAC2 NAMING STRUCTURE

HVFD2D 3 C 0000 E2



SPECIFICATION TAKE-OFF SERVICE

Put our product experts to work for you.

CREATED FOR YOU

With Honeywell's Specification Take-Off Service, you can submit your building drawings, specifications or schedules to have a take-off performed by our field device product experts.

The team will analyze your project and develop a completed schedule that includes base pricing and product specifications. The project schedule is provided to you at no cost, leaving you more time to get more work done.

Any Honeywell contractor or distributor in North America can use the Take-Off Service.

WE PROVIDE

Documents included with most takeoffs:

- Product schedule
- Part numbers
- Submittal documents
- Honeywell base price
- Quote ID
- Ordering instructions

EASY TO USE

The Honeywell Take-Off Service can create product schedules from:

- Product specifications
- Existing schedules
- Drawings
- Obsolete or competitive schedules

Whether your project is large and complex or as simple as a few line items, our goal is to provide you with the best possible solution for each job.

EASY TO USE

Commercial water and steam valves, pressure independent control valves, valve and damper actuators (electric and pneumatic), variable frequency drives.

The Take-off Service can also provide quotes for valves that are not standard Honeywell products. Contact us for details.



CREATED FOR YOU

Submit your information to takeoff.service@honeywell.com. Please include:

- Product schedule
- Part numbers
- Submittal documents

Our technical team will perform the Take-Off Service and send you a quote.

Please note, however, that the quality of the submitted information largely determines the turn-around time. We will work closely with you to ensure that we have enough information to move forward as quickly as possible.

SPECIFICATION TAKE-OFF SERVICE

Email: takeoff.service@honeywell.com

Hours:

Monday thru Friday
7:30 a.m. to 3:30 p.m. CST

CONFIGURE, PRICE, QUOTE: CPQ SELECT

Configure, price, and quote Honeywell Field Devices from a single, easy-to-use tool.

Easy to Use CPQ Features

- Quickly find and select the right product for your application
- Compare specifications across different products
- View and download technical literature
- Configure and tag valve assemblies
- Create quotations and save automatically to the cloud for future projects
- Export simple quotations or include full submittal documentation

Honeywell Commercial Products Include

- Control Valves & Actuator
- Actuators – Direct Coupled Actuators (DCA) and Foot Mounted
- Variable Frequency Drives (VFDs)
- Sensors
- Submeters
- Standalone Controllers
- Pneumatics
- Thermostats
- Building Automation

Product Selection and Quoting Made Easy



Configure Price Quote

WWW.CPQ.HONEYWELL.COM

CONTACT INFORMATION AND WEBSITES

Customer eCommerce Site

mybuildings.honeywell.com

Commercial Components Technical Hotline

888-516-9347

BuildingsProductSupport@Honeywell.com

Literature Ordering

literature.honeywell.com

Configure, Price, Quote (CPQ)

cpq.honeywell.com

Specification Take-Off Service

takeoff.service@honeywell.com

Learn More

buildings.honeywell.com/bms

Honeywell Building Technologies

715 Peachtree St NE

Atlanta, Georgia 30308

buildings.honeywell.com

BMS-BR-ValveSelectionGuide | 67-7382 | 2021-05-10
© 2021 Honeywell International Inc.

Honeywell