Intrinsically Safe Call Point Range

IS-MCP1 Resistor & Clean Contact Model (Red Versions)





- Unique 'Plug & Play' installation concept
- Total 'Flex-Ability' in the choice of operating element
- Anti-Tamper facility
- Enhanced aesthetics
- Fully approved to the latest standards
- Backward compatibility







Product Overview

An Intrinsically Safe version of our MCP1A indoor call point is available for installation in hazardous areas. These call points are manufactured to protect against other hazards, as defined in paragraph 1.2.7 of annex II of the ATEX Directive 94/9/EC. They are intended for use within Intrinsically Safe (I.S.) systems using suitable I.S. barriers. For a list of suitable barriers see reverse.

Installation efficiency, flexibility and full compliance with the latest standards are at the heart of the new Indoor Call Point range.

Installation time and ultimately cost, are of paramount importance to any fire or security installer. The MCP range directly reflects this need by providing a unique 'plug and play' concept designed specifically to reduce installation time. All new MCP products utilise a special terminal block, where all initial installation cabling is terminated. This terminal block is then simply connected to the back of the MCP. Simple, but effective with no re-termination required and no time wasted.

Through new standards and legislation, both break glass and resettable operating elements can now be used within a manual call point. To provide you with the greatest 'flex-ability', the new MCP range can be configured as either a break glass or resettable unit by simply changing from one element to another. No other additional parts or alternative products need to be ordered.

All MCP Indoor Call Point products also help preserve the integrity of the overall system as illegal removal of the product lid will result in the call point operating and the system going in to alarm.

The MCP1A product version is supplied with both a resistor and normally open clean contact electrical options. These options are easily utilised by simply connecting the terminal block to the required connection in the back of the MCP1 product. A variety of resistor versions are available, with both 470Ω and 680Ω offered as standard. However, other resistor types can be provided upon request. The MCP1B product version allows for connection to 'Savwire' systems.







Connection Details: See Figure .1 0.5-2.5mm² Cable Termination: Maximum Voltage: 30VDC 500mA Maximum current:

Maximum Power: 1W

Certification Details: II 1 G EEx ia II C T4

Sira 04ATEX2350X

Suitable IS Barriers:

KFDO-Cs-Ex 1.51P (BAS98ATEX7343), KFDO-Cs-Ex 2.51P (BAS98ATEX7343) Pepperl & Fuchs -

MTL4061 (BAS01ATEX7176), MTL5061 (BAS01ATEX7160) MTL -

A certified shunt zener barrier may be used having the following output parameters;

Uz - 28V, Imax - 93.3mA, Wmax - 0.67W

En

Humidity: 93± 3% non-condensing

Ambient Temperature Range: -10° C to + 55 $^{\circ}$ C


Ingress Protection (IP) Rating: IP24D

For RoHS, WEEE & REACH data please see www.kac.co.uk

PC/ABS Material: Weight: 130g Flush

180g Surface

Red, Ral 3001 Colour:







Figure .1

IS-MCP1A-X IS-MCP1B-X



Ordering Information

Model	Electrical Configuration	Mounting	Operating Element	Markings
MCP1A-R470FG-K013-01IS	470Ω Resistor & N\O 30VDC	Flush	Glass	EN54-11
MCP1A-R470FF-K013-01IS	470Ω Resistor & N\O 30VDC	Flush	Flexi	EN54-11
MCP1A-R470SG-K013-01IS	470Ω Resistor & N\O 30VDC	Surface	Glass	EN54-11
MCP1A-R470SF-K013-01IS	470Ω Resistor & N\O 30VDC	Surface	Flexi	EN54-11
MCP1B-R470SF-K013-01IS	470Ω Resistor & N\O 30VDC (SAV)	Surface	Flexi	EN54-11
MCP1A is also available with a 680 Ω resistor				

N\O = Normally Open Contact (SAV) = Savwire system

Accessories

Code Description

SC070 Pack Of Ten Test Keys

KG1 x 5 Pack Of Five Glass Elements (Also available in packs of 10, 25 & 50)

Flexible Operating Element PS210 PS200 Plain Hinged Cover

SC071 Pack Of Twenty Terminal Blocks



> Learn More: kac.co.uk